

Indoor Model	Vitocal 222-A AWOT-M-E 221.A16
Outdoor Model	Vitocal 200-A AWO-M-E 201.A16
Air-to-water heat pump	yes
Water-to-water heat pump	no
Brine-to-water heat pump	no
Low-temperature heat pump	no
Equipped with a supplementary heater	yes
Heat pump combination heater	yes



Application	Low temperature
Climate conditions	Average

Rated heat output	Prated	11	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	Pdh	9.4	kW
Tj = + 2 °C	Pdh	5.7	kW
Tj = + 7 °C	Pdh	8.9	kW
Tj = + 12 °C	Pdh	6.7	kW
Tj = bivalent temperature	Pdh	9.4	kW
Tj = operation limit temperature	Pdh	8.5	kW
Tj = - 15 °C (if TOL < -20 °C)	Pdh		kW
Bivalent temperature	T _{biv}	-7	°C
Cycling interval capacity for heating	P _{psych}		kW
Degradation coefficient	Cdh	0.98	
Power consumption in modes other than active mode			
Off mode	P _{OFF}	0.059	kW
Thermostat-off mode	P _{TO}	0.000	kW
Standby mode	P _{SB}	0.025	kW
Crankcase heater mode	P _{CK}	0.000	kW
Other items			
Capacity control		variable	
Sound power level, indoors/outdoors	L _{WA}	39/56	dB
Annual energy consumption	Q _{HE}	5152	kWh

Seasonal space heating energy efficiency	η _s	175	%
Declared coefficient of performance for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	COP _d	3.1	
Tj = + 2 °C	COP _d	4.3	
Tj = + 7 °C	COP _d	5.7	
Tj = + 12 °C	COP _d	7.7	
Tj = bivalent temperature	COP _d	3.1	
Tj = operation limit temperature	COP _d	2.8	
Tj = - 15 °C (if TOL < -20 °C)	COP _d		
Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP _{psych}		
Heating water operating limit temperature	WTOL	60	°C
Supplementary heater			
Rated heat output	P _{sup}	9.0	kW
Type of energy input		Electric	
Rated air flow rate, outdoors			
		4500	m ³ /h

For heat pump combination heater			
Declared load profile			
		L	
Daily electric consumption	Q _{elec}	4.234	kWh
Annual electricity consumption	AEC	904	kWh
Standby cylinder heat loss		1200	Wh/day

Water heating energy efficiency	η _{wh}	117	%
Daily fuel consumption	Q _{fuel}		kWh
Annual fuel consumption	AFC		kWh
Reference hot water temperature		52.5	°C
DHW volume accounted for in test		290	l

Application	Medium temperature
Climate conditions	Average

Rated heat output	Prated	10	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	Pdh	4.6	kW
Tj = + 2 °C	Pdh	3.1	kW
Tj = + 7 °C	Pdh	3	kW
Tj = + 12 °C	Pdh	2.9	kW
Tj = bivalent temperature	Pdh	4.6	kW
Tj = operation limit temperature	Pdh	4.4	kW
Tj = - 15 °C (if TOL < -20 °C)	Pdh		kW
Bivalent temperature	T _{biv}	-7	°C
Cycling interval capacity for heating	P _{psych}		kW
Degradation coefficient	Cdh	0.98	
Power consumption in modes other than active mode			
Off mode	P _{OFF}	0.059	kW
Thermostat-off mode	P _{TO}	0.000	kW
Standby mode	P _{SB}	0.025	kW
Crankcase heater mode	P _{CK}	0.000	kW
Other items			
Capacity control		variable	
Sound power level, indoors/outdoors	L _{WA}	39/56	dB
Annual energy consumption	Q _{HE}	6524	kWh

Seasonal space heating energy efficiency	η _s	130	%
Declared coefficient of performance for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	COP _d	2.1	
Tj = + 2 °C	COP _d	3.2	
Tj = + 7 °C	COP _d	4.3	
Tj = + 12 °C	COP _d	5.6	
Tj = bivalent temperature	COP _d	2.1	
Tj = operation limit temperature	COP _d	1.9	
Tj = - 15 °C (if TOL < -20 °C)	COP _d		
Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP _{psych}		
Heating water operating limit temperature	WTOL	60	°C
Supplementary heater			
Rated heat output	P _{sup}	9.0	kW
Type of energy input		Electric	
Rated air flow rate, outdoors			
		4500	m ³ /h

For heat pump combination heater			
Declared load profile			
		L	
Daily electric consumption	Q _{elec}	4.234	kWh
Annual electricity consumption	AEC	904	kWh
Standby cylinder heat loss		1200	Wh/day

Water heating energy efficiency	η _{wh}	117	%
Daily fuel consumption	Q _{fuel}		kWh
Annual fuel consumption	AFC		kWh
Reference hot water temperature		52.5	°C
DHW volume accounted for in test		290	l